


Universal accessories 30 mm
1. Purpose of the product and general information.

Universal accessories 30 mm - material used in combination with siding Döcke LUX Stone, Facade and socle panels Döcke at exterior cladding.

2. Geometric and logistical characteristics of universal accessories 30 mm.

№	Element	Picture	Purpose of use and geometrical parameters	Gross weight of one package, kg	Quantity in pack, pcs	Outside package dimensions (LxWxH), mm	Package type
1	Window & Door Trim 89/30 mm, 3m		Finishing of window and door openings. Length – 3,0 m.	21,4	16	3026x306x146	Corrugated cardboard box
2	Outer Corner 75/30 mm		Finishing the outer corners of the building. Length – 3,0 m.	16,8	8	3026x353x136	Corrugated cardboard box
3	Universal Window Trim 89/254 mm, 3 m		Finishing of window and door openings. Used with J-Channel & Finish Strip. Length – 3,0 m.	23,8	12	3026x296x126	Corrugated cardboard box
4	J-Channel 18 mm		Auxiliary element used as: -Finishing trim of panels; -Finishing the inner corners of the building; -Element in non-standard cases. Used with facade panels FLEMISH, BERG, BURG, KLINKER. Length – 3,0 m.	14,8	20	3026x156x146	Corrugated cardboard box
5	J-Channel 26 mm		Auxiliary element used as: -Finishing trim of panels; -Finishing the inner corners of the building; -Element in non-standard cases. Used with facade panels STEIN, STERN, DUFOUR, SHALE, ALTAI Length – 3,0 m.	12	20	3026x156x146	Corrugated cardboard box

№	Element	Picture	Purpose of use and geometrical parameters	Gross weight of one package, kg	Quantity in pack, pcs	Outside package dimensions (LxWxH), mm	Package type
6	J-Channel 30 mm		Auxiliary element used as: -Finishing trim of panels; -Finishing the inner corners of the building; -Element in non-standard cases. Used with facade panels FELS and siding LUX Stone Length – 3,0 m.	25	36	3026x306x146	Corrugated cardboard box

3. Storage rules.

- Products transportation must be carried out on vehicles with covered or tilt bodies, not shorter than the length of the transported material.
- The product must be stored only in the manufacturer original packaging.
- Store packages on a solid, continuous surface that is at least as long as the siding packaging. Do not allow the packs to overhang at the edges.
- The product must be stored in conditions that prevent moisture and direct sunlight.
- The product must be stored only in covered rooms with ventilation, at temperatures from -35 °C to +50 °C and relative humidity 50-60%.
- For long-term storage (more than 10 days), it is necessary to use pallets or shelving, while the boxes stacking height should not exceed 1,5 m.
- It is strictly forbidden to store products:
 - without packaging;
 - in direct sunlight;
 - near heating devices (at a distance of less than 1,5 m).

Technical support: 8 800 100 71 45, www.docke.ru.