

Siding Döcke LUX Stone

1. Purpose of the product and general information.






Siding Döcke LUX Stone is an exterior cladding material from PVC designed to protect the building's facade from the effects of climatic and environmental factors.



2. Siding Döcke LUX Stone geometrical and logistics characteristics.

№	Element	Length, m	Width, mm	Profile Height, mm	Area, m ²	Gross weight of one package, kg	Quantity in pack, pcs	Outside package dimensions (LxWxH), mm	Package type
1	BERGART	1,809	285	28	0,52	18,9	14	1926x318x358	Corrugated cardboard box
2	ROCKY	1,787	285	41	0,51	16,2	12	1926x318x358	Corrugated cardboard box

3. Döcke LUX accessories (used with siding LUX Stone). Geometric and logistical characteristics.

№	Element	Picture	Purpose of use and geometrical parameters	Gross weight of one package, kg	Quantity in pack, pcs	Outside package dimensions (LxWxH), mm	Package type
1	BERGART Corner		Finishing of the outer corners of the building faced with Döcke LUX stone-designed siding Length – 424 mm.	5,2	8	480x180x480	Corrugated cardboard box
2	ROCKY Corner		Finishing of the outer corners of the building faced with Döcke LUX stone-designed siding Length – 400 mm.	5,2	9	530x215x435	Corrugated cardboard box
3	Starter Strip		The starting element for the siding LUX Stone fixation. Length – 3000 mm.	24	66	3026x156x146	Corrugated cardboard box
4	Starter Corner DUFOUR		Starting element for fixing BERGART corners at the outer corners of the building.	1,8	50	226x226x206	Corrugated cardboard box
5	Starter Corner STEIN, STERN, SHALE, ALTAI		Starting element for fixing ROCKY corners at the outer corners of the building.	1,9	50	226x226x206	Corrugated cardboard box

4. Storage rules.

- Products transportation must be carried out on vehicles with covered or tilt bodies, not shorter than the length of the transported material.
- The product must be stored only in the manufacturer original packaging.
- The product must be stored in conditions that prevent moisture and direct sunlight.
- The product must be stored only in covered rooms with ventilation, at temperatures from -35 °C to +50 °C and relative humidity 50-60%.
- For long-term storage (more than 10 days), it is necessary to use pallets or shelving, while the boxes stacking height should not exceed 1,5 m.
- It is strictly forbidden to store products:
 - without packaging;
 - in direct sunlight;
 - near heating devices (at a distance of less than 1,5 m).

Technical support: 8 800 100 71 45, www.docke.ru.